



Dickey Manufacturing Company

Assure Tight 23R



Assure Tight 23R Seals are versatile, easy to use, and are a fully adjustable plastic seal. The thin, smooth tail can fit through small openings. Unlike beaded or ratcheting tail seals, the Assure Tight seal can be adjusted tightly to any length. The tail is secured with a metal one direction locking mechanism for a positively secured seal.

The built in tear tab allows for easy tool-less removal.

APPLICATIONS

- ↗ Cabinets & Lockers
- ↗ Cash & Coin bags
- ↗ Containers
- ↗ Fiber drums
- ↗ Truck & Railcar doors
- ↗ Liquid bulk trailers
- ↗ Liquor carts
- ↗ Transfer hoppers
- ↗ Valves

PACKAGING

- ↗ Up to 5000 Seals per case
- ↗ Weight per 1000: 5.5 lbs

SPECIFICATIONS

- ↗ Materials: Polypropylene, metal locking mechanism
- ↗ Operational length: variable
- ↗ Minimum required slot size: ~0.1"
- ↗ Average breaking strength: 36 lbs
- ↗ Numbering: to 8 digits
- ↗ Lettered SECURED

FEATURES

- ↗ Corrosion proof
- ↗ Enclosed metal locking mechanism
- ↗ Multi-locking positions
- ↗ No sealing tools needed
- ↗ Ultraviolet inhibitors and antioxidants added to extend life
- ↗ Stock seals available for rush shipments
- ↗ Stock seals are marked with sequential numbering
- ↗ Self release tab for tool-less removal
- ↗ Stock item available in red, blue, green, yellow, & orange
- ↗ 9.3" overall length 6.3" usable

LOCKING INSTRUCTIONS

- ↗ Pass narrow end of seal through the openings of the item to be sealed
- ↗ Insert and push the end of the seal into and through the locking barrel
- ↗ Pull remainder of the seal through until the seal fits tightly on the item that you are sealing
- ↗ Gently tug on the seal to ensure the locking mechanism is properly seated
- ↗ Record seal number as required
- ↗ To remove pull the release tab downward away from flag



